

## Data / Specification Sheet • Camprofile Gaskets

**Camprofile gaskets** consist of a metal core, generally of stainless steel, with concentric grooves on either side. A sealing layer is usually applied on both sides, and depending on the duty the material for this layer can be graphite, PTFE (Teflon), Mica, Novus Therm or soft alloys like aluminium or silver. The sealing material layers protect the flange surfaces from damage as well as providing an excellent seal.



### Properties

Camprofile gaskets have a wide seating stress range which makes them:

- Highly suitable for varying temperatures and pressures
- Less sensitive to assembly faults (inaccurate bolt tensioning)
- Suitable for both light and heavy designed flanges
- Temperature resistant up to approx 1000°C dependent on layer material
- Resistant to media pressures up to 250 bar
- When assembled the remaining thickness of the sealing material is extremely low (0.1 - 0.2mm) thus reducing leaks, fail rates and environmental pollution
- Will not damage flange surface and is easily removed
- Camprofile cores are re-usable after cleaning, inspection, profile tracing and relayering with new sealing material. This is of particular interest in the case of costly heat exchanger gaskets when using Monel and other exotic materials
- Reduces maintenance costs and leakage.

### Seating stress

The following seating stress ranges offer reliable and effective performance.

Layer Material	Seating Stress (20°C)		
	Minimum (N/mm <sup>2</sup> )	Optimum (N/mm <sup>2</sup> )	Maximum (N/mm <sup>2</sup> )
Graphite	20	90	400
PTFE	20	90	400
Non Asbestos	40	125	400
Silver	125	240	450

The above values are based on parallel root form gaskets. The values have slight variations for convex root form gasket.

### Flange Surface

The recommended flange surface finish for camprofiles with sealing layers is from 3.2 to 6.3um Ra (125-250 RMS), also referred to as a smooth finish, however stock finish is acceptable.

### Core Thickness

Core thickness depends on the assembly circumstances. When a camprofile is replacing an existing gasket, the use of a 4mm thick core (M21L and M41L) should not be problematic. Only in exceptional situations using a thicker gasket might cause unnecessary stress on existing pipe runs, especially in rigid systems.

Piping System	Core Thickness (mm)	Thickness after assembly Core + Layers (mm)
Existing	3 (recommended)	Approx 3.1 - 3.4
New	4	Approx 4.1 - 4.4

Styles M21LM and M41LM are available in 4mm thickness only due to their construction.

As the company's products are used for a multiplicity of purposes and as the company has no control over the method of their applications or use, the company excludes all conditions or warranties, expressed or implied by statute or otherwise, as to their products and/or their fitness for any particular purpose. Any technical co-operation between the company and the customer is given for customers assistance only, and without liability on the part of the company.