



Novus Sealing Pty Ltd T/A **Novus Sealing**

15 Vinnicombe Drive,

P.O.Box 1541

Canning Vale WA 6155

**Tel (08) 9455 2155**

**Fax (08) 9455 2165**

ABN 28 057 426 909

Email: [mailbox@novussealing.com.au](mailto:mailbox@novussealing.com.au)

Website: [www.novussealing.com.au](http://www.novussealing.com.au)

# Technical Data Sheet

## Chutex Rubber

<b>Polymer</b>	<b>NR</b>
<b>Colour</b>	<b>Pink</b>
<b>Durometer</b>	<b>45° +/-5 Shore A</b>
<b>Specific Gravity</b>	<b>1.05</b>
<b>Tensile Strength</b>	<b>17 Mpa minimum</b>
<b>Elongation</b>	<b>550% minimum</b>
<b>Surface</b>	<b>Smooth</b>
<b>Temperature</b>	<b>Range -20°C to 70°C</b>

- **Pink coloured, soft (40 duro), natural rubber**
- **Excellent resistance to small particle and wet slurry abrasion**
- **Uses include chute and tank linings, pulley lagging, launders and troughs.**

### Chemical Resistance

<b>Weathering and Ozone</b>	<b>Fair</b>
<b>Abrasion</b>	<b>Excellent</b>
<b>Acids</b>	<b>Fair</b>
<b>Caustics/Alkalis</b>	<b>Good</b>
<b>Oil &amp; Petroleum Products</b>	<b>Poor</b>
<b>Organic Solvents</b>	<b>Not Recommended</b>

**THE ABOVE SPECIFICATIONS ARE A GUIDE ONLY**