

## **Data / Specification Sheet • Unipac 3**

CARBONIZED FIBER IMPREGNATED WITH PTFE & GRAPHITE LUBRICATE BRAIDED PACKING

**UNIPAC 3** 



Unipac 3 is made of carbonized fiber which is impregnated with PTFE dispersion and graphite lubricant. It is inert to almost all corrosive chemicals. When it is used for pumps, frictional heat is freely conducted to the stuffing box metal because of its excellent thermal conductivity, and thus no damage will be caused to the packing.

It can replace PTFE asbestos packing within wide service range.

It can be used to seal corrosive fluids except strong oxidizer acids, organic solvents, fluids where contamination is not permissible for centrifugal pumps, plunger pumps, mixers vales, etc.

Performance					
Temp (°C)	Press(Mpa)			Speed	DU
	Pump	Recipro- Pump	Valve	(m/s)	PH
290	4	15	20	20	0~14
Main applications					
Pump	Recipro.Pum p	Mixer	Valve	● 1 <sup>St</sup> Recommendation	
•	•	•	•	○ 2 <sup>nd</sup> Recommendation	

The Uni-Pac range of high quality performance compression packing's are designed to provide a seal between a moving spindle or shaft and the pressurized housing in which it operates.

Uni-Pac utilizes the most advanced production techniques and materials to ensure a high integrity seal is achieved even in the most demanding of industries. They are typically used on valve, rotary and reciprocating pumps.

Uni-Pac packing is available in a range of materials and is supplied in square section from 3mm to 25mm as standard with other sizes available on request. Standard boxes are supplied in 8 metres, with Unipac 7 and Unipac 10 also available in 1 metre handy packs.

As Novus Sealing products are used for multiple purposes and as the company has no control over the method of applications or use, Novus Sealing excludes all conditions or warranties expressed or implied by statute or otherwise as to their products and/or their fitness for any particular purpose. Any technical co-operation between the company and the customer is given for customers assistance only and without liability on the part of Novus Sealing.

Tel: +61 (08) 9455 2155 Fax:: +61 (08) 9455 2165 <u>www.novussealing.com.au</u> mailbox@novussealing.com.au