

Data / Specification Sheet • Unipac 2220

RAMIE IMPRENATED WITH PTFE BRAIDED PACKING

UNIPAC 2220



Diagonally braided from natural Ramie fibre, densely impregnated with a PTFE compound lubricant.

Very versatile packing for rotary & reciprocating pumps and also suitable for valves. Can be used in many different industries including pulp & paper, marine and food industry. Unipac 2220 is an excellent packing for stern glands and rudder post glands.

Performance					
Temp (°C)	Pressure (Bar)			Speed (m/s)	PH
	Pump	Reciprocating Pump	Valve		
-50 - 130	50	80	100	10	4~12
Main applications					
Pump	Reciprocating Pump	Mixer	Valve	● 1 st Recommendation	
●	●	○	○	○ 2 nd Recommendation	

The Uni-Pac range of high quality performance compression packing's are designed to provide a seal between a moving spindle or shaft and the pressurized housing in which it operates.

Uni-Pac utilizes the most advanced production techniques and materials to ensure a high integrity seal is achieved even in the most demanding of industries. They are typically used on valve, rotary and reciprocating pumps.

Uni-Pac packing is available in a range of materials and is supplied in square section from 3mm to 25mm as standard with other sizes available on request. Standard boxes are supplied in 8 metres, with Unipac 7 and Unipac 10 also available in 1 metre handy packs.

As Novus Sealing products are used for multiple purposes and as the company has no control over the method of applications or use, Novus Sealing excludes all conditions or warranties expressed or implied by statute or otherwise as to their products and/or their fitness for any particular purpose. Any technical co-operation between the company and the customer is given for customers assistance only and without liability on the part of Novus Sealing.