

Data / Specification Sheet • SUREBAND Clear

SUREBAND Clear is ideal for Acid / Caustic / E15 Oil and Diesel mist prevention

Manufactured from All-PTFE materials (no fibreglass) comprising clear ETFE outer and multi-layered ECTFE mesh inner. This material provides unparalleled chemical resistance. All our shields are tested on our hydrostatic pressure test facility, test certificates available on request.

The internal mesh is compressed against the flange and prevents direct and lateral spray. The liquid pressure inside is rapidly diffused, resulting in a safe drip-release.


SUREBAND Clear is very quick to install using heavy duty Velcro tabs which have been leak tested at various orifice sizes at pressure up to 75 Bar. It can be re-used in the event of a leak, thus providing a long term solution.

Specifications

Band Material:	ETFE
Mesh Material:	ECTFE
Fastener:	Heavy Duty Velcro
Shear force:	196 N
Max Temperature:	230 Deg C
Flange Ratings: Pipe	ANSI / DIN / many others
Sizes:	15mm to 1200mm
Leak Detection:	Visual Litmus Paper
Typical Applications:	Acid, Bases, Oil



This product can also be made to fit valves and other non-standard pipe joints, contact Novus Sealing for further information.



As the company's products are used for a multiplicity of purposes and as the company has no control over the method of their applications or use, the company excludes all conditions or warranties, expressed or implied by statute or otherwise, as to their products and/or their fitness for any particular purpose. Any technical co-operation between the company and the customer is given for customers assistance only, and without liability on the part of the company.