


GRAPHITE/PTFE WITH ARAMID IN CORNERS

UNIPAC 5



Novus Unipac 5 is a high-quality braided packing made of PTFE yarns fiber incorporated with graphite and reinforced corner yarns of Aramid fiber. It can prevent gaps from extrusions in the presence of high pressure and temperature. It has good sliding velocity and thermal conductivity. It enables to seal high pressure piston pumps during long running periods.

It can be used seal water, sewage water, hot water, oils, greases, weak acids and alkaline solutions and abrasive media.

Performance					
Temp (°C)	Pressure (Bar)			Speed (m/s)	PH
	Pump	Recipro- Pump	Valve		
-100~280	40	200	250	20	2~12
Main applications					
Pump	Recipro.Pump	Mixer	Valve	● 1 st Recommendation	
●	●	●	●	○ 2 nd Recommendation	

The Uni-Pac range of high quality performance compression packing's are designed to provide a seal between a moving spindle or shaft and the pressurized housing in which it operates.

Uni-Pac utilizes the most advanced production techniques and materials to ensure a high integrity seal is achieved even in the most demanding of industries. They are typically used on valve, rotary and reciprocating pumps.

Uni-Pac packing is available in a range of materials and is supplied in square section from 3mm to 25mm as standard with other sizes available on request. Standard boxes are supplied in 8 metres, with Unipac 7 and Unipac 2240 also available in 1 metre handy packs.

As the company's products are used for multiplicity of purposes, and as the company has no control over the method of their applications or use, the company excludes all conditions or warranties, expressed or implied by statute or otherwise, as to their products and/or their fitness for any particular purpose.

Any technical co-operation between the company and the customer is given for customers assistance only and without liability on the part of the company.

As the company's products are used for multiplicity of purposes, and as the company has no control over the method of their applications or use, the company excludes all conditions or warranties, expressed or implied by statute or otherwise, as to their products and/or their fitness for any particular purpose.

Any technical co-operation between the company and the customer is given for customers assistance only and without liability on the part of the company.