

Data / Specification Sheet • Unipac 7

FIBERGLASS IMPRENATED WITH GRAPHITE BRAIDED PACKING

UNIPAC 7



Made from fiberglass yarn and impregnated with a special composite with high percentage graphite base with a slight addition of lubricant and corrosion inhibitor.

For use in dynamic and general applications. Well suited to a small range of valve and pump duties where the use of non-contaminating packing is not important.

Performance					
Temp (°C)	Pressure (Bar)			Speed (m/s)	PH
	Pump	Reciprocating Pump	Valve		
590	10	70	100	2	4~11
Main applications					
Pump	Reciprocating Pump	Mixer	Valve	● 1 st Recommendation	
○	○	●	●	○ 2 nd Recommendation	

The Uni-Pac range of high quality performance compression packing's are designed to provide a seal between a moving spindle or shaft and the pressurized housing in which it operates.

Uni-Pac utilizes the most advanced production techniques and materials to ensure a high integrity seal is achieved even in the most demanding of industries. They are typically used on valve, rotary and reciprocating pumps.

Uni-Pac packing is available in a range of materials and is supplied in square section from 3mm to 25mm as standard with other sizes available on request. Standard boxes are supplied in 8 metres, with Unipac 7 and Unipac 2240 also available in 1 metre handy packs.

As Novus Sealing products are used for multiple purposes and as the company has no control over the method of applications or use, Novus Sealing excludes all conditions or warranties expressed or implied by statute or otherwise as to their products and/or their fitness for any particular purpose. Any technical co-operation between the company and the customer is given for customers assistance only and without liability on the part of Novus Sealing.