



Novus Sealing Pty Ltd

15 Vinnicombe Drive,

P.O.Box 1541

Canning Vale WA 6155

Tel (08) 9455 2155

Fax (08) 9455 2165

ACN 057 426 909

ABN 28 057 426 909

Email: mailbox@novussealing.com.au

Virgin PTFE Product

Virgin PTFE contains no fillers and has almost universal chemical resistance. It has excellent insulating capabilities and high dielectric properties. Its high temperature stability allows for continuous use at 260°C. Virgin PTFE has excellent low friction, non-stick and release properties.

Virgin PTFE Applications:

- O-Rings
- Envelope gaskets
- Seals
- Bellows
- Linings (chemical)
- Valve seats

Physical Properties:

Specific Gravity:	g/cm ³	2.18
Max Continuous Operating Temp:	°C	260
Max Short Term Operating Temp (3-4hrs):	°C	310
Tensile Strength:	Mpa	28
Hardness:	Rockwell M	65
Co-efficient of thermal expansion:	m/(m.k) x 10 ⁻⁶	125
Dielectric Strength:	KV/mm	59
Surface Resistivity:	Ohms >	10 ^{^7}
Flammability UL94:		530
Food Grade:	FDA	Yes

As Novus Sealings products are used for multiple purposes and as the company has no control over the method of applications or use, Novus Sealing excludes all conditions or warranties expressed or implied by statute or otherwise as to their products and/or their fitness for any particular purpose. Any technical co-operation between the company and the customer is given for customers assistance only and without liability on the part of Novus Sealing.